

CAUTION Keep out of reach of children
Read safety directions before opening



REFUSAL

MULTI FUNCTIONAL INDUSTRIAL SOLVENT

UN 1992 HAZCHEM CODE 3WE PACKAGING GROUP III

Cyndan Refusal is a complex blend of solvents which can be rinsed away with water. The result of this complex blend brings a lengthy list of applications to which Cyndan Refusal can be used. Cyndan Refusal will remove many inks and greases and oils and can control insects and growth fungi. For this reason this label is very detailed and diverse in its application recommendations.

DIRECTIONS:

GRAFFITI REMOVAL: Best applied by spray method. Direct the spray at graffiti with force. The jet spray applications allows total penetration thus dissolving graffiti instantly. Rinse with water.

SEWAGE PLANT: For grease control. a) Dilute with 50 parts water, spray over sludge beds, trickling filters, lagoons, oxidation ponds and digesters, b) Use Refusal for this application at full strength. Drip feeding is the best application. Allow the neat Cyndan Refusal to drip into system at a rate of 1:5 parts per million parts of sewage.

GREASE TRAPS, SINKS, DRAINS, ETC: Dilute at rate of 1 litre to 25 litres water. Pour dilution down all pipes to be cleared. Allow if possible this solution to sit in drains and pipes for 30-60 minutes.

REFUSE TRUCKS, EQUIPMENT, BINS: For clearing equipment apply by spray, dip or brush method. Agitate and rinse with water. Dilutions as much as one part Refusal to 500 parts water may be used depending on the degree of degreasing required.

SAFETY: Avoid contact with eyes.

FIRST AID: If swallowed, do NOT induce vomiting, give a glass of water and seek medical attention. Contact the Poisons Information Centre (13 11 26 Australia; 0800 764 766 New Zealand). If in eyes, hold eyelids open and flush with water for at least 15 minutes.

Batch #:

* Trademark



CYNDAN
chemical solutions



9 343310 007316

Cyndan Chemicals 1/7 Jubilee Avenue Warriewood NSW 2102 AUSTRALIA ph +61 2 9998 5688 www.cyndan.com.au