



# Masonry Sealer - Clear

## Penetrating concrete and brick waterproofing sealer

Sealing compound to seal and protect any masonry surface. Penetrates surfaces and seals out grease, oil and battery acid. Prevents absorption of unwanted substances, eliminating foul odours, unsightly staining and slip. May be applied as a clear protective coating over hazard safety lines in warehouse and factory areas. Recommended for workshop floors, tiled bathroom and shower block floors (including urinal steps), car parks, food processing

# 5LT

Best before Dec 2021  
1234567

M S E - X U - 3 - 1 0 0 - K B - 0 0 5 - L T M



## Directions for use:

### Coverage:

About 6 square metres per litre.

### Dilution:

First coat for dense surfaces: 1 part to 3 parts Xylene.

1. Remove any loose contamination, dust, etc.
2. Ensure surface is silicone-free and oil-free.
3. Ensure the surface is completely dry before application.
4. Apply with a brush or low-pressure sprayer, ensuring even coverage.
5. Allow 20 to 30 minutes between coats.
6. Apply 2 or 3 coats if a light lustre is desirable.

**Notes:** One good even coat is sufficient to seal. Ideal ambient temperatures for application are 10°C to 30°C. Avoid applying in windy conditions. Do not apply if rain is likely within 12 hours.