

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.

SAFETY: Keep away from heat and flames. Do not inhale. Wear gloves and protective clothing. Keep container tightly closed.

FIRST AID: If poisoning occurs, contact a doctor or Poisons Information Centre (Australia 13 11 26, New Zealand 0800 764 766) and have this label to hand. If swallowed, do not induce vomiting; instead provide a glass of water. If in eyes, flood with water for at least 15 minutes. If on skin, wash skin and clothing thoroughly.

SPILLS & LEAKS: Clear area of all unprotected personnel. Slippery when spilt. Wear protective equipment. Absorb with sand or soil. Collect and seal in properly labelled drums. Refer to State/Territory Land Waste Management Authority for disposal.

FIRE: If material is involved in a fire use alcohol resistant foam, standard foam or dry agent (carbon dioxide, dry chemical powder).

POISON

Keep out of reach of children
Read safety directions before opening

Masonry Sealer - Yellow

Emergency telephone number:

+61 (0)2-9998 5656

**In a transport emergency dial 000 Police or
Fire Brigade**

DO NOT REUSE CONTAINER UNLESS THOROUGHLY DECONTAMINATED. SEE THE SAFETY DATA SHEET FOR ADDITIONAL INFORMATION

UN No: 1993

FLAMMABLE LIQUID, N.O.S.
(XYLENE; 2-METHOXY-1-
METHYLETHYL ACETATE)

CONTAINS: >60% XYLENE; 10-30% TURPENTINE OIL; 1-10% SOLVENT
NAPHTHA, PETROLEUM, LIGHT AROMATIC.

