



Rust Buster - Silver

Rust encapsulator and neutraliser for corrosion prevention

UV-resistant formula penetrates the pores of rust and bonds to metal substrate. Dries clear, leaving a solid, pore-free surface which prevents further corrosion for up to 8 years. Use on marine vessels, steel roofs, silos, bridges, containers, structural steel, pipelines. May be applied to metals to be immersed in water, when overcoated with suitable paint.

1LT

Best before Dec 2021
1234567

R B S - M U - 3 - 0 9 7 - K B - 0 0 1 - L T M



Directions for use:

Coverage:

Heavily rusted surfaces: 12 to 15 sq m per litre.
Lightly rusted surfaces: 20 to 25 sq m per litre.
Sound painted surfaces: 30 sq m per litre.

As an overcoat for UV resistance: Apply over clear Cyndan Rust Buster as second coat after 2 hours.

1. Ensure surface is dry, free from grease, mill scale, loose rust and flaky paint. For severe rusting, clean steel with sand, soda or water blasting. Remove mill scale by pickling compound or blasting.
2. Immediately before use, stir until a uniform consistency is achieved.
3. Apply light coats with a brush, roller or airless spray gun. Allow 2 hours between coats.
4. Apply a third coat if the second coat is not glossy when dry.

Clean up: Mineral turpentine or paint thinners.

Drying time: Allow 24 hours before overpainting.

Note: Please see the Technical Data Sheet on our website for full details.