

**CAUTION** Keep out of reach of children  
Read safety directions before opening

# Graffiti Armour Solvent

100% Naphtha

UN	1268	HAZCHEM CODE	3[Y]	PACKAGING GROUP	III
----	------	--------------	------	-----------------	-----



## DIRECTIONS:

**FOR SPRAY APPLICATION:** Due to the high viscosity of the base product "Graffiti Armour" and that the base product starts to dry and cure quite quickly when it is exposed to air, (temperature and humidity will affect this), it is best mixed (shaken well) with the solvent in a sealed container.

However this does introduce air into the mixture. This air requires settlement before spraying commences to allow a smooth spray mixture. An example would be for a 50/50 mixture of Graffiti Armour + solvent, to a settling time approximately 8 hours will remove most air bubbles, 12 hours leaves just the odd few bubbles.

Mixtures of lesser viscosity (more solvent) require less settling time, greater viscosity (less solvent) require longer settling time.

Therefore it is advised to mix 24 hours before spraying, depending on the application, to remove all of the air bubbles.

**SAFETY:** Flammable. Keep away from sources of ignition – No Smoking. Avoid contact with eyes and skin. Wear protective clothing, gloves and eye protection.

**FIRST AID:** If swallowed, do NOT induce vomiting, give a glass of water and seek medical attention. Contact the Poisons Information Centre (13 11 26 Australia; 0800 764 766 New Zealand). If in eyes, hold eyelids open and flush with water for at least 15 minutes. If skin contact occurs, remove contaminated clothing and rinse for 15 minutes with soap and water. Ensure clothing is washed thoroughly before using again.

Batch #: 1613713

\* Trademark

1L



**CYN DAN**  
chemical solutions



9 343310 012754