

CAUTION Keep out of reach of children
Read safety directions before opening

LUBE & COOL

MACHINE LUBRICANT AND COOLANT

Cyndan Lube & Cool combines both lubrication and cooling of machine parts during all machine operations. Cyndan Lube & Cool results in cooler, cleaner cuts, promotes longer tool life and excellent surface finish.

DIRECTIONS:

Before using Cyndan Lube & Cool it is advisable to remove old coolant and debris from the sump or coolant reservoir. When diluted Cyndan Lube & Cool always add Cyndan Lube & Cool to the water and mix thoroughly.

	WATER	LUBE & COOL
Lathe Operations	25	1
Milling	30	1
Drilling	35	1
Grinding	50	1
Tapping	20	1
Threading	20	1
Broaching	20	1

SAFETY: Avoid contact with eyes.

FIRST AID: If swallowed, do NOT induce vomiting, give a glass of water and seek medical attention. Contact the Poisons Information Centre (13 11 26 Australia; 0800 764 766 New Zealand). If in eyes, hold eyelids open and flush with water for at least 15 minutes.

Batch #:

* Trademark



9 343310 005541

Cyndan Chemicals 1/7 Jubilee Avenue Warriewood NSW 2102 AUSTRALIA ph +61 2 9998 5688 www.cyndan.com.au