

CAUTION Keep out of reach of children
Read safety directions before opening

TIMBER PROTECTION SOLUTION

Cyndan Timber Protection Solution is a marine grade, water resistant deep penetrating clear timber treatment. Cyndan Timber Protection Solution is ideal for all natural timbers and is especially suited for application to Teak used in marine environments.

DIRECTIONS:

Before application the surface should be dry, free of dirt, oil, dust and any other contaminants. If the surface has an existing coating or varnish, this should be stripped off by sanding back for a bare timber application. The application objective is to get maximum penetration into the timber surface with each treatment pass. After the surface is prepared adequately, apply using a lambs wool floor applicator or roller and saturate the surface with the product and allow to soak in for 10 - 20 minutes. Then using a clean cotton rag or lambs wool applicator wipe over the area until the product has completely penetrated the timber. Allowing at least 12 hours between treatment applications. Apply up to 3 treatments sanding lightly between the second and third application. One treatment is sufficient, however the additional application will build on the first providing deeper colour and longer protection. Depending on the timber additional treatments may produce a gloss finish.

SAFETY: Avoid contact with eyes.

FIRST AID: If swallowed, do NOT induce vomiting, give a glass of water and seek medical attention. Contact the Poisons Information Centre (13 11 26 Australia; 0800 764 766 New Zealand). If in eyes, hold eyelids open and flush with water for at least 15 minutes.

Batch #:

* Trademark

15 Litre



CYNDAN
chemical solutions



9 343310 010132

Cyndan Chemicals 1/7 Jubilee Avenue Warriewood NSW 2102 AUSTRALIA ph +61 2 9998 5688 www.cyndan.com.au